


9" SL 9" fine bubbles disc diffuser with EPDM membrane and integrated

ring nut



Dimensions

Code	04059
Outer diameter [mm]	257
Threaded connection	3/4" NPT
Weight [Kg]	0,43

Performance

Code		04059
Minimum airflow	$[Nm^3/h]$	1,0
Nominal airflow	$[Nm^3/h]$	3,5
Maximum airflow	$[Nm^3/h]$	7,0
Design airflow range	[Nm ³ /h]	2,0-4,0
* Head losses [cm w.c.]		39,0


* Head losses are calculated at nominal airflow and 4m submergence

Materials

Code	04059
Membrane	EPDM
Holder	PPGF 30%

Data subject to change without notice

WTE SRL Via Re Depaolini,52 • 20015 Parabiago (MI) Italy



Membrane

Code	04059	NOTES
Number of slits	>5.000	SOTE according
Perforation [mm]	1,0-1,5	to ANSI/ASCE-06 (EN 12255-15)
Active surface [m ²]	0,0381	Tollerances on the
Average thickness [mm]	2,2	thickness ±0,2 mm
Tensile strength [Kg/cm²]	>126	Tensile strenght
Elongation at break [%]	540	according to ISO 37 type 1
Hardness [Shore A]	60	Elongation at break
Plasticizer content [%]	< 15	ISO 37 type 1

